US007925309B2

US 7,925,309 B2

(12) **United States Patent**
Söderlund

(10) **Patent No.:** **US 7,925,309 B2**
(45) **Date of Patent:** **Apr. 12, 2011**

(54) **ROTATABLE MODULE WITH TWO INPUT DEVICES FOR A MOBILE COMMUNICATION APPARATUS**

(75) Inventor: **Marcus Söderlund**, Stockholm (SE)

(73) Assignee: **Sony Ericsson Mobile Communications AB**, Lund (SE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 818 days.

(21) Appl. No.: **11/721,987**

(22) PCT Filed: **Dec. 15, 2005**

(86) PCT No.: **PCT/EP2005/056812**
§ 371 (c)(1),
(2), (4) Date: **Nov. 14, 2007**

(87) PCT Pub. No.: **WO2006/067081**
PCT Pub. Date: **Jun. 29, 2006**

(65) **Prior Publication Data**
US 2009/0264152 A1   Oct. 22, 2009

(30) **Foreign Application Priority Data**

Dec. 21, 2004   (EP) 04030376

(51) **Int. Cl.**
H04M 1/00   (2006.01)
H01R 13/60   (2006.01)
H01R 13/66   (2006.01)
B65H 75/48   (2006.01)
(52) **U.S. Cl.** **455/575.1**; 455/575.3; 379/438; 439/528; 242/378.1

(58) **Field of Classification Search** 455/575.1, 455/575.3, 575.4, 90.3; 379/438; 439/528; 242/378.1
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,483,723	B2 *	1/2009	Soderlund	.... 455/575.1
2004/0142734	A1	7/2004	Kim	
2004/0176047	A1	9/2004	Trively	
2005/0239520	A1 *	10/2005	Stefansen	.... 455/575.1

FOREIGN PATENT DOCUMENTS

EP	1 339 203	8/2003
WO	2004/036881	4/2004

OTHER PUBLICATIONS

International Search Report for corresponding Application No. PCT/EP2005/056812 mailed Apr. 24, 2006.

* cited by examiner

Primary Examiner — Un C Cho
(74) *Attorney, Agent, or Firm* — Renner, Otto, Boisselle & Sklar, LLP

(57) **ABSTRACT**

A portable electronic device (**1**) comprising a first portion (**3, 53**) including at least one output device (**2**) for rendering output data and a second portion (**4, 54**) comprising at least two input devices (**10, 11, 20, 30, 40**) for manually inputting data into the portable electronic device. The second portion is rotatably connected to the first portion. The output device is directed in the same direction as a first input device when the second portion is positioned in a first position, and in the same direction as another input device when the second portion is positioned in a second position.

8 Claims, 7 Drawing Sheets